# **COMMERCIAL DATA SHEET Quadra Compact Firewall**



## Billi Quadra Compact with Firewall Tower Dispenser

The Quadra Compact Boiling and Chilled drinking water system is a water cooled, high capacity, intermediate population commercial drinking water solution that maintains the core Billi design principles and requires no joinery ventilation. The drawcard for the entire Quadra range is the use of innovative energy reclaim technology which enables space savings, energy efficiency and completely eliminates exhaust heat transfer. All Quadra boiling and chilled products are Global GreenTag certified to a Gold standard.

Ideal for patients and residents in health and aged-care environments, the Firewall® Tower Dispenser offers a unique above bench tower design, to guarantee 99.99% pure water, 100% of the time. The system leverages UVC technology uniquely positioned at the point of dispense, rendering waterborne bacteria incapable of reproduction, moments before it is delivered.

The Firewall® Tower Dispenser also features BioCote® technology that protects surfaces against bacteria, mould and fungi. There is no need to specify a carbon free filter to support the bactericidal & virucidal effect of the Firewall Tower dispenser.













Firewall Tower Dispenser







## **Features**











SPACE SAVING DESIGN

**ENERGY** 

WATER COOLED TECHNOLOGY

**EXCHANGE TECHNOLOGY** 











VENTILATION REQUIRED

AUSTRALIAN DESIGNED & MADE

# PRODUCT SPECIFICATIONS

| Water<br>type   | Product<br>code | Model<br>name                           | Suggested<br>number<br>of people | Boiling water<br>delivery<br>(cups per hour)* | Chilled water<br>delivery<br>(cups per hour) | Power supply (amps) |
|-----------------|-----------------|---|----------------------------------|---|--|---------------------|
| POLINIC CHILLED | 904010FT        | Quadra Compact Firewall Tower Dispenser | Up to 20                         | 100   | 150  | 1x10<br>1x10        |


Based on the initial number of cups of boiling water immediately available, drawn one cup every 10 seconds. For all under bench filtered water systems, consideration may be needed for usage patterns and draw-off methods. 1 cup = 170ml.

## Accessories

## **TECHNICAL DRAWING & INSTALLATION REQUIREMENTS**

## PRODUCT DIMENSIONS

# DISPENSER 385mm 125mm 225mm



## **WATER SUPPLY**

A single 1/2" BSP (15mm) stop-tap with a male thread should be installed in an easily accessible position. Water supply must be microbiologically safe to drink, with a minimum dynamic water pressure of 250kPa and a maximum of 1000kPa.


## **POWER SUPPLY**

A standard 10 amp power outlet is required for the underbench PLUS a standard 10 amp power outlet for the Firewall Tower dispenser. Both outlets located no further than 1000mm from the underbench unit. The system is supplied with a 1 metre flex cord and plug.

## **FILTRATION**

Billi's range of premium filters utilise BWT's unique Fibron X technology. Billi's filter range provides superior taste, water quality, consistent filter life and peace of mind when it comes to hygiene. Filter supplied: 994051 (5 micron). Replacement filters available: 994052 (0.2 micron), 994054 (HSD), 994055 (XPHSD), 994056 (Sediment only) and 994060 (0.2 micron sediment only).

## PREFERRED INSTALLATION LAYOUT



## **CERTIFICATIONS**

Every Billi drinking water appliance is manufactured under a certified quality control system. All Billi commercial range models have been tested and comply with all required standards including: Watermark: WM-021525;

Certified to AS/NZ3498 and AS/NZ 4020;

ISO9001:2015, QEC 11627;

Section J6.6 of the BCA;

Global GreenTag LCARate Gold;

HACCP: PE-872-WAT-1-02:

NSF P231 for Microbiological Purification;

NSF/ANSI 55 Class A;

WELL Cornerstone Member.

## WARRANTY

The Billi Quadra Range is covered by a comprehensive 2 year warranty on all parts and labour.



















Billi Australia Pty Ltd 42 Lucknow Crescent, Thomastown, Victoria 3074 Australia

P 1800 812 321 F +61 3 9469 0499 W www.billi.com.au



