

# Billi™

---

User guide

Billi Alpine 060 and Alpine 120

(932060, 932120)



# User guide

## Billi Alpine 060 and Alpine 120.

---

### Contents

Warnings & Important information	2
General Maintenance	3
Features and Modes	3
Filtration Information	3
Changing the filter	4
Service Support	5

### Warnings & Important information

- For continued safety of this appliance it must be installed, operated and maintained in accordance with the manufacturer's instructions.
- Your appliance should be installed by a suitably qualified tradesperson.
- For correct operation of this appliance it is essential to observe the instructions as outlined in this booklet.
- Do not use this appliance with water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.
- Filter replacement must be performed at intervals of not more than 12 months.
- Use this appliance only as directed in these instructions and only for its designed purpose.
- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
- Children should be supervised to ensure that they do not play with the appliance.
- If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid creation of a hazard.
- New hose sets supplied with the appliance are to be used. Old hose sets should not be re-used.
- The appliance is intended to be used in household and similar applications such as:
  - Staff kitchen areas in shops, offices and other working environments
  - Farm houses and by clients in residential type environments
  - Bed and breakfast type environments
  - Catering and similar non-retail applications
- **WARNING:** When positioning the appliance, ensure the supply cord is not trapped or damaged.
- **WARNING:** Do not locate multiple portable socket - outlets or portable power supplies at the rear of the appliance.
- **WARNING:** Avoid spillage on the connector.
- **WARNING:** Potential injury from misuse.

**Please note maximum water inlet pressure is 1 MPa**

# User guide

## Billi Alpine 060 and Alpine 120.

---

### General Maintenance

Your Billi Alpine has been designed to require minimal maintenance other than replacement of filter cartridges. During each filter change, check all water connection fittings for signs of leakage. Check all tubing for any signs of damage. Check the cupboard area around the base of unit for any signs of moisture.

### Cleaning the dispenser

Your Alpine Dispenser is fabricated from robust metal with a tough protect chrome plating. Care of dispenser is as with any chrome plated tapware. Avoid using abrasive cleaners. Wipe clean using a damp cloth. Use of a non-solvent, non-smearing cleaner such as Windex is recommended. Do not pour water over dispenser.

### Cupboard ventilation requirements

Your Billi Alpine underbench module is designed to not require any cupboard ventilation or air space around the unit; simplifying installation and space requirements. However, care should be taken when using the cupboard space, to avoid stretching or damaging plastic pipe work. Check fittings and tubing at each filter change for signs of damage or leakage. Always ensure access to power switch and water supply tap is not restricted.

### Features and Modes

#### Slimline Dispenser

To dispense filtered water, the dispenser tap lever will need to be rotated. The lever will automatically return to the off position. The spout can be swivelled to suit your installation.

#### Adjustable chilled water temperature

The chilled water delivery temperature can be adjusted to suit your preference. The blue control knob, located on the front of the Chiller Module, can be adjusted if a cooler or warmer temperature is required.

### Billi Filter Cartridges

The Billi Alpine uses environmentally friendly, element-type cartridges. The two-stage system includes a Sediment Removal pre-filter and Chemical Removal post-filter.

#### Use only genuine Billi Filter Cartridges as designed for this system.

If the system has not been used for a period of 3 days or more, lift the dispenser lever and flush the system for at least 1 minute.

# User guide

## Billi Alpine 060 and Alpine 120.

---

### Filter Cartridges Service Interval

Periodic replacement of your Billi Alpine filter cartridge is necessary to maintain the sparkling freshness of your drinking water.

Your Billi Representative will advise you of an appropriate service interval. As a guide, the filters should be serviced twice yearly. In areas where water supply has a high level of sediment, more frequent replacement of filter cartridges may be necessary. This will become evident when a significant drop in delivery flow rate occurs.

### Filter Cartridge Replacement

When you receive your replacement cartridges, follow the procedure as outlined below:

1. Turn off water supply to unit.
2. Remove front panel to unit.
3. Turn temperature control to OFF
4. Open tap to release any pressure.
5. Close tap.
6. Grasp the bottom of the filter and pull towards yourself slowly. The top of the filter is in a hinged cradle assembly. It should stop after approximately 30 degrees of travel.
7. The filter can now be released from the holding cradle by pulling down on the filter.
8. Take care not to spill water in the base of the tray. If so wipe gently with blotting paper.
9. Install new filter into the same location by pushing up into the cradle all the way.
10. Push filter forward until upright and locked in place.
11. Turn water supply to unit on.
12. Open tap again.
13. Run water for 2-3 minutes to flush all air out and condition the filter.
14. Close tap.
15. Check for any leaks from around the filter, hosing or pipe work.
16. Turn temp control to ON & set temperature to desired level.
17. Close front cover.

# User guide

## Billi Alpine 060 and Alpine 120.

---

Thank you for choosing to install a Billi Alpine Drinking Water Appliance. Your Alpine is manufactured to exacting standards using high quality materials and with proper maintenance and care, should function for many years.

For information on our filtration and service contract please contact Billi Head Office on 1800 812 321 or email us at [service@billi.com.au](mailto:service@billi.com.au).

For technical support please call 1800 812 321 and speak to one of Billi's experienced technician's.

To book a service call out request a filter change or please contact the Billi Service Centre on 1800 812 321 or book online at [www.billi.com.au](http://www.billi.com.au)

Filter cartridges are also available for purchase online at [www.billi.com.au](http://www.billi.com.au)





# Billi™

---

**Billi Australia Pty Ltd**  
42 Lucknow Crescent, Thomastown  
Victoria 3074 Australia

Telephone 1800 812 321

[www.billi.com.au](http://www.billi.com.au)

Designed and manufactured in Australia.

As Billi Australia Pty Ltd has a policy of continual improvement, all details are subject to change without notice. All goods are sold subject to our published terms and conditions. Billi is a registered trademark. 1220